

**BOSTIK PVC PRIMING FLUID RED**  
Revision Number 2Revision date 27-Jan-2020  
Supersedes Date: 28-Aug-2016**Section 1: Identification: Product identifier and chemical identity****Product identifier****Product Name** BOSTIK PVC PRIMING FLUID RED**Product Code(s)**30840469  
30840469; 30840470; 30840471; 30840472; 30840489**Other means of identification****Proper Shipping Name** Flammable liquid, n.o.s. (Methyl ethyl ketone, Acetone)**UN Number** UN1993**Pure substance/mixture** Mixture**Recommended use of the chemical and restrictions on use****Recommended use** No information available**Uses advised against** No information available**Details of manufacturer or importer****Supplier**Bostik Australia Pty Ltd  
51-71 High Street,  
Thomastown Victoria  
Australia  
Tel: 613 9279-9333  
Fax: 613 9279-9342**ABN:** 79 003 893 838**E-mail address** au-bostik-sds@bostik.com**Emergency telephone number**

Emergency telephone number 24-hr Emergency: 1800 033 111

**Section 2: Hazard(s) identification****GHS Classification**

Based on available information, this material is classified as hazardous according to criteria of Safe Work Australia

<b>Flammable liquids</b>	Category 2 - (H225)
<b>Serious eye damage/eye irritation</b>	Category 2A - (H319)
<b>Specific target organ toxicity (single exposure)</b>	Category 3 - (H336)

**Label elements**Flame  
Exclamation mark

# SAFETY DATA SHEET

BOSTIK PVC PRIMING FLUID RED  
Revision Number 2

Revision date 27-Jan-2020  
Supersedes Date: 28-Aug-2016



**Signal word**  
Danger

## **Hazard statements**

H225 - Highly flammable liquid and vapor  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness  
AUH066 - Repeated exposure may cause skin dryness or cracking

## **Precautionary Statements - Prevention**

P264 - Wash face, hands and any exposed skin thoroughly after handling  
P280 - Wear protective gloves/protective clothing/eye protection/face protection  
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray  
P271 - Use only outdoors or in a well-ventilated area  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P235 - Keep cool  
P241 - Use explosion-proof electrical/ ventilating/ lighting/ equipment  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P337 + P313 - If eye irritation persists: Get medical advice/attention  
P303 + P361 + P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
P312 - Call a POISON CENTER or doctor/physician if you feel unwell  
P370 + P378 - In case of fire: Use CO2, dry chemical, or foam to extinguish

## **Precautionary Statements - Storage**

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed  
P405 - Store locked up

## **Precautionary Statements - Disposal**

P501 - Dispose of contents/ container to an approved waste disposal plant

## **Other hazards which do not result in classification**

May be harmful if swallowed

## **Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)**

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

**Poison Schedule Number** S5

## **Label requirements in accordance with SUSMP**

CAUTION  
KEEP OUT OF REACH OF CHILDREN  
READ SAFETY DIRECTIONS BEFORE OPENING OR USING

## **Section 3: Composition and information on ingredients, in accordance with Schedule 8**

### **Substance**

Not applicable

# SAFETY DATA SHEET

BOSTIK PVC PRIMING FLUID RED  
Revision Number 2

Revision date 27-Jan-2020  
Supersedes Date: 28-Aug-2016

## Mixture

Chemical name	CAS No.	Weight-%
Methyl ethyl ketone	78-93-3	30 - 60
Acetone	67-64-1	30 - 60

## **Section 4: First aid measures**

**Emergency telephone number** Poisons Information Center, Australia: 13 11 26  
Poisons Information Center, New Zealand: 0800 764 766

### **FIRST AID**

**General advice** Show this safety data sheet to the doctor in attendance.

**Inhalation** Remove to fresh air. Get medical attention immediately if symptoms occur.

**Eye contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

**Skin contact** Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

**Ingestion** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Clean mouth with water. Drink 1 or 2 glasses of water. Call a physician or poison control center immediately.

**Self-protection of the first aider** Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

### **Most important symptoms and effects, both acute and delayed**

**Symptoms** Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

### **Indication of any immediate medical attention and special treatment needed**

**Note to physicians** Treat symptomatically.

## **Section 5: Firefighting measures**

### **Suitable extinguishing media**

**Suitable extinguishing media** Dry chemical. Carbon dioxide (CO<sub>2</sub>). Water spray. Alcohol resistant foam.

**Unsuitable extinguishing media** Do not use straight streams. CAUTION: Use of water spray when fighting fire may be inefficient.

### **Specific hazards arising from the chemical**

**Specific hazards arising from the chemical** Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

**Hazardous combustion products** Carbon oxides.

# SAFETY DATA SHEET

BOSTIK PVC PRIMING FLUID RED  
Revision Number 2

Revision date 27-Jan-2020  
Supersedes Date: 28-Aug-2016

## Special protective actions for fire-fighters

**Special protective equipment for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## **Section 6: Accidental release measures**

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Evacuate personnel to safe areas. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Avoid breathing vapors or mists. Ensure adequate ventilation. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded.

**Other information** Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

**For emergency responders** Use personal protection recommended in Section 8.

### Environmental precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not allow to enter into soil/subsoil.

### Methods and material for containment and cleaning up

**Methods for containment** Dike far ahead of spill; use dry sand to contain the flow of material. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

**Methods for cleaning up** Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Take up mechanically, placing in appropriate containers for disposal.

### Precautions to prevent secondary hazards

**Prevention of secondary hazards** Eliminate all ignition sources if safe to do so.

## **Section 7: Handling and storage, including how the chemical may be safely used**

### Precautions for safe handling

**Advice on safe handling** Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. In case of insufficient ventilation, wear suitable respiratory equipment.

**General hygiene considerations** Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations.

# SAFETY DATA SHEET

BOSTIK PVC PRIMING FLUID RED  
Revision Number 2

Revision date 27-Jan-2020  
Supersedes Date: 28-Aug-2016

**Incompatible materials** None known based on information supplied.

This material is a scheduled poison and must be stored, maintained and used in accordance with the relevant regulations

## Section 8: Exposure controls and personal protection

### Control parameters

### Exposure Limits

Chemical name	Australia
Methyl ethyl ketone 78-93-3	150 ppm TWA 445 mg/m <sup>3</sup> TWA 300 ppm STEL 890 mg/m <sup>3</sup> STEL
Acetone 67-64-1	500 ppm TWA 1185 mg/m <sup>3</sup> TWA 1000 ppm STEL 2375 mg/m <sup>3</sup> STEL

OEL as published by Safe Work Australia

### Appropriate engineering controls

**Engineering controls** Showers  
Eyewash stations  
Ventilation systems.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Tight sealing safety goggles.

**Skin and body protection** Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.  
Antistatic boots.

**Hand protection** Wear suitable gloves. Impervious gloves.

**Respiratory protection** No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

**Environmental exposure controls** No information available.

## Section 9: Physical and chemical properties

### Information on basic physical and chemical properties

**Physical state** Liquid  
**Appearance** Liquid  
**Color** Red  
**Odor** Ketone  
**Odor threshold** No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	
Melting point / freezing point	No data available	
Boiling point / boiling range	56 °C	
Flash point	-17 °C	CC (closed cup)
Evaporation rate	No data available	
Flammability (solid, gas)	Not applicable for liquids	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	

# SAFETY DATA SHEET

BOSTIK PVC PRIMING FLUID RED  
Revision Number 2

Revision date 27-Jan-2020  
Supersedes Date: 28-Aug-2016

Lower flammability or explosive limits	No data available
Vapor pressure	No data available
Vapor density	No data available
Relative density	No data available
Water solubility	Slightly soluble
Solubility(ies)	No data available
Partition coefficient	No data available
Autoignition temperature	No data available
Decomposition temperature	No data available
Kinematic viscosity	No data available
Dynamic viscosity	No data available
Explosive properties	No information available
Oxidizing properties	No information available

## Other information

Solid content (%)	No information available
VOC Content (%)	405 g/L
Density	0.8 g/cm <sup>3</sup>

## **Section 10: Stability and reactivity**

### Reactivity

Reactivity No information available.

### Chemical stability

Stability Stable under normal conditions.

### Explosion Data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	Yes.

### Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

### Conditions to avoid

Conditions to avoid Heat, flames and sparks.

### Incompatible materials

Incompatible materials None known based on information supplied.

### Hazardous decomposition products

Hazardous decomposition products Carbon oxides. Nitrogen oxides (NOx). Thermal decomposition can lead to release of irritating and toxic gases and vapors.

## **Section 11: Toxicological information**

### Acute Toxicity

### Information on likely routes of exposure

#### Product Information

Inhalation May cause irritation of respiratory tract. May cause drowsiness or dizziness.

# SAFETY DATA SHEET

BOSTIK PVC PRIMING FLUID RED  
Revision Number 2

Revision date 27-Jan-2020  
Supersedes Date: 28-Aug-2016

<b>Eye contact</b>	Causes serious eye irritation. May cause redness, itching, and pain.
<b>Skin contact</b>	May cause irritation. Prolonged contact may cause redness and irritation.
<b>Ingestion</b>	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
<b>Symptoms</b>	May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

## Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 4,929.60 mg/kg

## Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl ethyl ketone	=2483 mg/kg (Rattus)	= 5000 mg/kg (Oryctolagus cuniculus)	=11700 ppm (Rattus) 4 h
Acetone	=5800 mg/kg (Rattus)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h

See section 16 for terms and abbreviations

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Skin corrosion/irritation</b>	May cause skin irritation.
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.
<b>Respiratory or skin sensitization</b>	No information available.
<b>Germ cell mutagenicity</b>	No information available.
<b>Carcinogenicity</b>	No information available.
<b>Reproductive toxicity</b>	No information available.
<b>STOT - single exposure</b>	May cause drowsiness or dizziness.
<b>STOT - repeated exposure</b>	No information available.
<b>Aspiration hazard</b>	No information available.

## Section 12: Ecological information

### Ecotoxicity

#### Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Methyl ethyl ketone 78-93-3	EC50=1972 mg/l (Pseudokirchneriella subcapitata)	LC50: 3130 - 3320mg/L (96h, Pimephales promelas)	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50 48 h > 308 mg/L (Daphnia magna )
Acetone 67-64-1	-	LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss )	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)

# SAFETY DATA SHEET

BOSTIK PVC PRIMING FLUID RED  
Revision Number 2

Revision date 27-Jan-2020  
Supersedes Date: 28-Aug-2016

## Persistence and degradability

**Persistence and degradability** No information available.

Component Information			
Methyl ethyl ketone (78-93-3)			
Method	Exposure time	Value	Results
OECD Test No. 301D: Ready Biodegradability: Closed Bottle Test (TG 301 D)	28 days	biodegradation	98 % Readily biodegradable

## Bioaccumulative potential

**Bioaccumulation** There is no data for this product.

## Component Information

Chemical name	Partition coefficient
Methyl ethyl ketone 78-93-3	0.3
Acetone 67-64-1	-0.24

## Mobility

**Mobility in soil** No information available.

**Mobility** No information available.

## Other Adverse Effects

**Other adverse effects** No information available.

## Section 13: Disposal considerations

### Waste treatment methods

**Waste from residues/unused products** Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

## Section 14: Transport information

### ADG

**UN Number** UN1993  
**Proper shipping name** Flammable liquid, n.o.s.  
**Hazard Class** 3  
**Packing Group** II  
**Special Provisions** 274  
**ADG Limited Quantity** 1 L  
**Description** UN1993, Flammable liquid, n.o.s. (Methyl ethyl ketone, Acetone), 3, II

### IATA

**UN number** UN1993  
**Transport hazard class(es)** 3  
**Packing group** II  
**ERG Code** 3H  
**Special Provisions** A3



# SAFETY DATA SHEET

BOSTIK PVC PRIMING FLUID RED  
Revision Number 2

Revision date 27-Jan-2020  
Supersedes Date: 28-Aug-2016

Limited Quantity (LQ) 1 L  
Description UN1993, Flammable liquid, n.o.s. (Methyl ethyl ketone, Acetone), 3, II

## IMDG

UN number UN1993  
Transport hazard class(es) 3  
Packing group II  
EmS-No. F-E, S-E  
Limited Quantity (LQ) 1 L  
Special Provisions 274  
Marine Pollutant Np  
Description UN1993, Flammable liquid, n.o.s. (Methyl ethyl ketone, Acetone), 3, II, (-17°C c.c.)

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

## Section 15: Regulatory information

### Safety, health and environmental regulations/legislation specific for the substance or mixture

#### National Regulations

##### Australia

See section 8 for national exposure control parameters

#### Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number S5

#### Major hazard (accident/incident planning) regulation

Verify that license requirements are met

#### Hazardous chemical

Liquids with flash points <61°C kept above their boiling points at ambient conditions

#### Threshold quantity (T)

200

#### National pollutant inventory

Subject to reporting requirement

Chemical name	National pollutant inventory
Methyl ethyl ketone 78-93-3	10 tonne/yr Threshold category 1 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total
Acetone 67-64-1	10 tonne/yr Threshold category 1 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total

#### International Inventories

AICS Listed  
NZIoC Listed  
ENCs Not Listed  
IECSC Not Listed

# SAFETY DATA SHEET

BOSTIK PVC PRIMING FLUID RED  
Revision Number 2

Revision date 27-Jan-2020  
Supersedes Date: 28-Aug-2016

KECL Not Listed  
PICCS Not Listed

## Legend:

**AICS** - Australian Inventory of Chemical Substances  
**NZIoC** - New Zealand Inventory of Chemicals  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

## International Regulations

**The Montreal Protocol on Substances that Deplete the Ozone Layer** Not applicable

**The Stockholm Convention on Persistent Organic Pollutants** Not applicable

**The Rotterdam Convention** Not applicable

## Section 16: Any other relevant information

Revision date 27-Jan-2020

### Revision note

The symbol (\*) in the margin of this SDS indicates that this line has been revised.

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

#### Section 11: TOXICOLOGICAL INFORMATION

LD50 (lethal dose)

#### Section 12: Ecological information

EC50 (effective concentration)

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**